

Blixer® 5 V.V.



5,9 L

A SALES FEATURES

Blixer® 5 V.V. is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer® 5 V.V. Single-phase. Power: 2 HP. Variable speed: 300-3500 rpm. 5.9 L stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Watertight lid with Blixer® arm. 3 - 20 portions (7 oz.).

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	2 HP
Electrical data	120V/60/1 - 5.8 Amps
Variable speed	300-3500 rpm
Dimensions (WxDxH)	10 7/16" x 13 25/64" x 21 17/64"
Rate of recyclability	95%
Net weight	47 lbs
Nema #	5-20P
Reference	BLIXER 5 V.V. - 120V/60/1

D

Number of 7 oz. portions per service



Amount processed per operation

0.75 to 7 lbs

E**PRODUCT FEATURES / BENEFITS****MOTOR UNIT**

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 2 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe.
- **Variable speed 300-3500 rpm**
- Pulse function for greater cutting precision

BLIXER® FUNCTION

- **5.9 L stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat and shock-resistant **see-through lid** to monitor processing from start to finish.
- Watertight bowl-lid assembly with Blixer® arm.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 5.9 L bowl with lid.
- Blixer® arm and lid wiper
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Blixer® 5 V.V.

F OPTIONAL ATTACHMENTS

- Additional bowl assembly: bowl, fine-serrated blade, lid and Blixer® arm - Ref 27322
- Coarse-serrated, twin-blade assembly for grinding and kneading - Ref. 27311
- Additional fine-serrated, twin-blade assembly - Ref. 27310

G ELECTRICAL DATA

120V/60/1 – delivered with cord and plug.

